

In re: Gammon
Serial No.: 10/615,096
Filed: July 8, 2002
Page 2 of 14

In the Claims:

1. (Currently Amended) A collapsible cargo storage apparatus for a vehicle interior having a seat that includes a seating area and a seat back that support a vehicle occupant, wherein the seating area has a generally concave, sloping contour, the cargo management system comprising:

a base configured to be supported by the seating area of the seat, wherein the base comprises opposite upper and lower surfaces, opposite front and rear portions, and opposite side portions, and wherein the base lower surface comprises a plurality of elongated, convex ribs of differing sizes extending therefrom in spaced-apart relationship, wherein the ribs has a generally convex, sloping contour that matingly engage engages the generally concave, sloping configuration of the a seating area contour in contacting relationship, wherein the ribs base lower surface contour helps help retain the storage apparatus on the seating area and reduce reduces the likelihood of the storage apparatus moving during vehicle movement;

a front panel pivotably attached to the base front portion via a hinge; and
a rear panel pivotably attached to the base rear portion via a hinge;

wherein the front and rear panels are each movable between a stored position and an operative position, wherein the front and rear panels extend generally perpendicular to the base for constraining motion of articles disposed on the base upper surface when in the operative position, wherein the front and rear panels overlie the base upper surface in a flat configuration when in the stored position, and wherein the rear panel is in contacting relationship with the seat back when in the operative position.

2. (Original) The storage apparatus of Claim 1, further comprising a pair of end panels pivotably attached to the respective base end portions, wherein each end panel is movable between a stored position and an operative position, wherein the end panels extend generally perpendicular to the base for constraining motion of articles disposed on the base upper surface when in the operative position, and wherein the end panels overlie the base upper surface in a flat configuration when in the stored position

In re: Gammon
Serial No.: 10/615,096
Filed: July 8, 2002
Page 3 of 14

3. (Cancelled)

4. (Original) The storage apparatus of Claim 1, wherein the rear panel has a contour that is configured to matingly engage a contour of a vehicle seat back when the storage apparatus is installed within a vehicle.

5. (Original) The storage apparatus of Claim 1, wherein the front and rear panels are pivotably attached to the base panel via respective hinges, and wherein the hinges are configured to bias the front and rear panels to respective operative positions.

6. (Original) The storage apparatus of Claim 2, wherein the front and rear panels are pivotably attached to the base panel via respective hinges, and wherein the hinges are configured to bias the front and rear panels to respective stored positions.

7. (Original) The storage apparatus of Claim 1, wherein the front panel has a first height, wherein the rear panel has a second height different from the first height.

8. (Previously Presented) The storage apparatus of Claim 2, wherein one or more of the front, rear and end panels comprises a storage pocket for receiving articles therein.

9. (Previously Presented) The storage apparatus of Claim 2, wherein one or more of the front, rear and end panels comprises at least one projection extending therefrom that is configured to support one or more loaded shopping bags by the handles thereof and to maintain the one or more loaded shopping bags in an upright position during operation of the vehicle.

10. (Original) The storage apparatus of Claim 1, further comprising a handle that facilitates carrying the apparatus when the front, rear and end panels are in respective stored positions.

In re: Gammon
Serial No.: 10/615,096
Filed: July 8, 2002
Page 4 of 14

11. (Currently Amended) A collapsible cargo storage apparatus for a vehicle interior having a rear seat, wherein the rear seat includes two adjacent seating areas and two corresponding seat backs that support vehicle occupants, wherein each seating area has a generally concave, sloping contour, the cargo management system comprising:

a base configured to be supported by the two adjacent seating areas of the rear seat, wherein the base comprises a pair of adjacent, substantially co-planar base panels separated by an intermediate portion, each base panel comprising opposite upper and lower surfaces, opposite front and rear portions, and a side portion, wherein the lower surface of each base panel comprises a plurality of elongated convex ribs of differing sizes extending therefrom in spaced-apart relationship, wherein the ribs has a generally convex, sloping contour that matingly engage engages the generally concave, sloping configuration of a respective seating area contour in contacting relationship, wherein the ribs contour of each lower surface help helps retain the storage apparatus on the seating area and reduce reduces the likelihood of the storage apparatus moving during vehicle movement, and wherein the base is configured to fold along the intermediate portion thereof such that the base panels are in adjacent, face-to-face relationship to facilitated storage;

a front panel pivotably attached to the front portion of each base panel; and

a rear panel pivotably attached to the rear portion of each base panel;

wherein the front and rear panels for each base panel are each movable between a stored position and an operative position, wherein the front and rear panels extend generally perpendicular to the respective base panel for constraining motion of articles disposed on the base panel upper surface when in the operative position, and wherein the front and rear panels overlie the respective base panel upper surface in a flat configuration when in the stored position, and wherein each rear panel is in contacting relationship with a respective seat back when in the operative position.

12. (Original) The storage apparatus of Claim 11, further comprising an end panel pivotably attached to a respective base panel side portion, wherein each end panel is movable between a stored position and an operative position, wherein each end panel

In re: Gammon
Serial No.: 10/615,096
Filed: July 8, 2002
Page 5 of 14

extends generally perpendicular to a respective base panel for constraining motion of articles disposed on the respective base panel upper surface when in the operative position, and wherein each end panel overlies the respective base panel upper surface in a flat configuration when in the stored position.

13. (Cancelled)

14. (Original) The storage apparatus of Claim 11, wherein the rear panel has a contour that is configured to matingly engage a contour of a vehicle seat back when the storage apparatus is installed within a vehicle.

15. (Original) The storage apparatus of Claim 11, wherein the respective front and rear panels are pivotably attached to the base panel via respective hinges, and wherein the hinges are configured to bias the respective front and rear panels to respective operative positions.

16. (Original) The storage apparatus of Claim 11, wherein the respective front and rear panels are pivotably attached to the base panel via respective hinges, and wherein the hinges are configured to bias the respective front and rear panels to respective stored positions.

17. (Original) The storage apparatus of Claim 11, wherein each front panel has a first height, wherein each rear panel has a second height different from the first height.

18. (Previously Presented) The storage apparatus of Claim 12, wherein one or more of the front, rear and end panels comprises a storage pocket for receiving articles therein.

In re: Gammon
Serial No.: 10/615,096
Filed: July 8, 2002
Page 6 of 14

19. (Previously Presented) The storage apparatus of Claim 12, wherein one or more of the front, rear and end panels comprises at least one projection extending therefrom that is configured to support one or more loaded shopping bags by the handles thereof and to maintain the one or more loaded shopping bags in an upright position during operation of the vehicle.

20. (Original) The storage apparatus of Claim 11, further comprising a handle attached to the base intermediate portion.

21. (Previously Presented) The storage apparatus of Claim 12, wherein one or more of the front, rear and end panels comprises cargo netting for restraining articles placed within the storage apparatus.